



# IPS e.max® CAD Abutment Solutions

Implant-supported hybrid restorations made of lithium-disilicate glass-ceramic for single tooth restoration

CTE (100 - 500 °C)\*

 $10.5\,\cdot\,10^{\text{--6}}\cdot\,K^{\text{--1}}$ 

BENDING STRENGTH\*

 $360 \pm 60 \text{ MPa}$ 





## INDICATIONS

- Hybrid abutments for anterior and posterior teeth
- Hybrid abutment crowns for anterior and posterior teeth

# BENEFITS

Order Number 001-4326EN

- + Hybrid abutment crown (2-in-1) for function, efficiency and easy access to the screw at any time
- + Precision fit due to CAD/CAM fabrication
- + Very good compatibility with the oral soft tissue
- + Excellent and long-lasting esthetics due to toothcoloured hybrid abutments

#### REFERENCES

Restorations made of IPS e.max® CAD Abutment Solutions can be customized in different ways. Please follow the manufacturer's instructions.

Note: IPS e.max® CAD Abutment Solutions are shipped in a non-crystalline state. They can be further processed in ceramic furnaces.

### COMPOSITION\*

SiO <sub>2</sub>	57.0 – 80.0 %
Li <sub>2</sub> O	11.0 – 19.0 %
K <sub>2</sub> O	0.0 – 13.0 %
Other	0.0 – 8.0 %